



Sullair Performance Lubricant

SULLAIR SRF II/8000[®]

Standard Replacement Fluid for Stationary Compressors



SRF II/8000 is a highly refined standard replacement fluid for stationary air compressors. This long-life hydro-treated petroleum-based fluid helps reduce maintenance, operation and disposal costs.

- Lasts long – up to 8000 hours or one year
- Resists breakdown from shearing and high temperatures

High quality — value priced

With excellent viscosity, SRF II/8000 is a high quality fluid offering high resistance to breakdown for stable operation at a wide range of temperatures. A hydro-treated fluid, it is highly demulsifiable, increasing the efficiency of oil/condensate separators. And SRF II/8000 is a good value for the money – providing budget-friendly long life.

FEATURES AND BENEFITS

Long lasting

Hydro-treated petroleum base resists breakdown and varnish.

Lubricates effectively

Excellent anti-wear properties are designed to provide longlasting lubrication.

Lowers expenses

Long changeout intervals cut maintenance labor and fluid disposal costs. Non-hazardous classification of used fluid reduces disposal costs further.

Comprehensive support

Sullair and our distributors stand ready with fluid professionals who can help you with any fluid-related issues or questions. Our exclusive Compressor Fluid Analysis program helps you evaluate your fluid and provides data to support your lubricant performance history, changeout intervals, and environmental conditions that may affect your fluid.

PRODUCT INFORMATION



| PACKAGING | |
|-----------|--------------|
| Size | Part Number |
| 5 Gallon | 02250118-160 |
| 55 Gallon | 02250118-162 |

| TYPICAL PROPERTIES | | |
|--------------------|---------------|------|
| Viscosity | 104°F (40°C) | 35.6 |
| | 212°F (100°C) | 5.7 |
| Flash Point | 431°F (222°C) | |
| Hours | 8000 | |



FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.



SULLAIR.COM   